

20V P-Channel Power MOSFET

UM2301S SOT23-3

UM2301P SOT323

General Description

The UM2301 is a low threshold P-channel MOSFET, have extremely low on-resistance. This benefit provides the designer with an extremely efficient device for use in battery and load management applications. The device uses a space-saving, small-outline SOT23-3 or SOT323 package.


Applications

- Battery Packs
- Battery-Powered Portable Equipments
- Cellular and Cordless Telephones


Features

- Drain-Source Voltage (Max): -20V
- Low On-Resistance:
200mΩ@V_{GS}=-4.5V
250mΩ@V_{GS}=-2.5V
- Continuous Drain Current (Max) :
-1.5A@25 °C (SOT23-3)
-1.1A@25 °C (SOT323)

Pin Configurations



Top View



Ordering Information

Part Number	Packaging Type	Marking Code	Shipping Qty
UM2301S	SOT23-3	10A	3000pcs/7 Inch Tape & Reel
UM2301P	SOT323	VLD	

Absolute Maximum Ratings

Symbol	Parameter	Value	Unit
V_{DSS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	± 8	V
I_D	Continuous Drain Current (5s)	SOT23-3	A
		SOT323	
I_{DP}	Drain Current Pulsed (Pulse Width $\leq 10\mu s$, Duty Cycle $\leq 1\%$)	-5	A
P_D	Power Dissipation	SOT23-3	W
		SOT323	
T_J	Junction Temperature	-55~150	$^{\circ}C$
T_{STG}	Storage Temperature	-55~150	$^{\circ}C$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient ($\leq 5s$)	SOT23-3	$^{\circ}C/W$
		SOT323	
ESD	ESD Method 3015.8	2000	V

Electrical Characteristics ($T_J=25^{\circ}C$, unless otherwise noted)


Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-to-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-20V, V _{GS} =0V			-0.1	μA
I _{GSS}	Gate-to-Source Leakage Current	V _{GS} =±8V, V _{DS} =0V			±10	μA
On Characteristics						
R _{DS(ON)}	Static Drain-to-Source On-Resistance (Note 1)	V _{GS} =-4.5V, I _D =-1.0A		200	350	mΩ
		V _{GS} =-2.5V, I _D =-1.0A		250	400	
V _{GS(TH)}	Gate-Source Threshold Voltage	V _{DS} = V _{GS} , I _D =-250μA	-0.4	-0.6	-1	V
g _{fs}	Forward Transconductance (Note 1)	V _{DS} =-5V, I _D =-2.0A		4.5		S
Dynamic Characteristics (Note 2)						
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =-10V, f=1.0MHz		405		pF
C _{oss}	Output Capacitance			150		
C _{rss}	Reverse Transfer Capacitance			55		
Switching Characteristics (Note 2)						
td(on)	Turn-on Delay Time	V _{DD} =-10V, R _L =10Ω, I _D =-1A, V _{GEN} =-4.5V, R _G =1Ω		11	20	ns
tr	Rise Time			35	60	
td(off)	Turn-off Delay Time			80	150	
tf	Fall Time			50	90	
Drain-Source Diode Characteristics and Maximum Ratings						
V _{SD}	Forward Diode Voltage	I _S =-0.7A		-0.8	-1.2	V

Note 1: Pulse test: pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.


Note 2: Guaranteed by design, not subject to production testing.

Typical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)


Output Characteristics




Transfer Characteristics



Source-Drain Diode Forward Voltage




On Resistance vs. Drain Current




Typical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)


On-Resistance vs. Gate-to-Source Voltage



On-Resistance vs. Ambient Temperature




Threshold Voltage vs. Ambient Temperature




Package Information

UM2301S SOT23-3

Outline Drawing



Land Pattern




Tape and Reel Orientation




UM2301P SOT323

Outline Drawing



Land Pattern



Tape and Reel Orientation



GREEN COMPLIANCE

Union Semiconductor is committed to environmental excellence in all aspects of its operations including meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Union components are compliant with the RoHS directive, which helps to support customers in their compliance with environmental directives. For more green compliance information, please visit:

http://www.union-ic.com/index.aspx?cat_code=RoHSDeclaration

IMPORTANT NOTICE

The information in this document has been carefully reviewed and is believed to be accurate. Nonetheless, this document is subject to change without notice. Union assumes no responsibility for any inaccuracies that may be contained in this document, and makes no commitment to update or to keep current the contained information, or to notify a person or organization of any update. Union reserves the right to make changes, at any time, in order to improve reliability, function or design and to attempt to supply the best product possible.